

The attached document is a portion 10446 as originally received. The entire original document, when scanned, was too large for most email programs.

Although the 4 four pages of 10446 are very hard to read, they contain background information on these notes and the surveying process.

RECORD # 10224
LANGLADE COUNTY SURVEYORS OFFICE
DATE FILED: 6/1/15 BY: D.T.

Dependent Resurvey, of the Third Parallel North, through Range 15, East, 4th Prin. Mer., Wisconsin.

Chains	
	N. 89° 57' W., along the S. bdy. of sec. 31. (West half mile.) Over rolling land, through heavy timber, and undergrowth.
13.12	The point for the standard cor. of Tps. 31N., Rs. 14 and 15 E., which is marked by a wooden post, 4 x 4 x 42 ins. above ground, set by a local surveyor for original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of Tps. 31 N., Rs. 14 and 15 E., with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd. S C T 31 N R 15 E S 36 S 31 1933 from which
	Remains of original bearing trees: A birch stump, 18 ins. diam., bears N. 75° E., 36 lks. dist., with old blaze, A sugar maple, 36 ins. diam., bears N. 72° W., 40 lks. dist., with scribe marks visible. And new bearing trees: A hemlock, 10 ins. diam., bears N. 64 1/2° E., 53 lks. dist., mkd., T 31 N R 15 S 31 SO 1/2 T, A yellow birch, 10 ins. diam., bears N. 65° W., 46 lks. dist., mkd., T 31 N R 15 S 36 SO 1/2 T. Land, E. 1/2 nearly level; W. 1/2 rolling, Soil, clay loam, 2nd tape. Timber, hemlock, sugar maple, elm, basswood, birch; undergrowth, young timber.
	Dependent Resurvey of the Third Standard Parallel North, through Range 14, East, as Originally Surveyed by James M. Marsh, U.S. Deputy Surveyor, in 1851.
	N. 89° 49' W., along the S. bdy. of Sec. 36, marking and blazing the true line, Over rolling land, with heavy timber to S., and out-over land to N., The true point for the closing cor. of secs. 4 and 5, after moving 5 lks. South, from its original position, as determined from the original bearing
36.99	

Dependent Resurvey of the Third Parallel
North, through Range 14, East, 4th Prin.
Mer., Wisconsin.

Chains	
40.16	trees, in order to place it on the true closing line. Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the closing cor. of secs. 4 and 5, Tp. 30 N., R. 15 E., with brass tablet, 2 1/2 ins. diam., 3 in. stem, embedded in top, mkd. T31N R14E S36 T30N R15E S34 T32N R15E S36 1933 from which
40.17	Remains of original bearing trees: A fallen hemlock, 20 ins. diam., bears S. 25° E., 26 lks. dist., with scribe marks. A basswood stump, rotted to ground, bears S. 20° W., 28 lks. dist. The point for the standard 1/4 sec. cor., as determined from original bearing trees. At point for cor., Set an iron post, 3 ft. long, 6 ins. diam., 27 ins. in the ground, for the standard 1/4 sec. cor., with brass bap. mkd. 1/4 S 36 1933 from which
40.18	Original bearing trees: A rock elm, 15 ins. diam., bears N. 64° E., 24 lks. dist., with overgrown blades. A sugar maple, 24 ins. diam., bears N. 58° W., 8 lks. dist., with old blades opened and scribe marks weathered off. And new bearing trees: A rock elm, 5 ins. diam., bears N. 24° W., 59 1/2 lks. dist., mkd. 1/4 S 36 SO B T. A rock elm, 16 ins. diam., bears N. 71° W., 94 lks. dist., mkd. 1/4 S 36 SO B T. N. 89° 50' W., along the S. bdy. of sec. 36, (west half mile.) Over gently rolling land. The point for the standard cor. of secs. 35 and 36, where I find the point of the original post. At point for cor., Set a concrete monument, 24 ins. long, 6 ins.

Dependent Resurvey of the Third Standard
Parallel, North, through Range 14, East,
4th Prin. Mer., Wisconsin.

diameter, 20 ins. in the ground, for the
standard cor. of secs. 35 and 36, with brass
tablet, $3\frac{1}{4}$ ins. diam., 3 in. stem, embedded in
top, mkd.

SC
T31N R14E
S35 E36

1933

from which

Original bearing trees:

A rock elm, 20 ins. diam., bears N. 22° E.,
23 lks. dist., with overgrown blaze.

A rock elm, 10 ins. diam., bears N. 37° W.,
20 lks. dist., with overgrown blaze.

A rock elm, 18 ins. diam., bears N. 69° W.,
37 lks. dist., with partly overgrown
blazes, and scribe marks visible.

And new bearing trees:

A hemlock, 6 ins. diam., bears N. 58° E., 8
lks. dist., mkd. T 31 N R 14 E S 36 SC B T.

A hemlock, 5 ins. diam., bears N. 49½° W.,
61 lks. dist., mkd. T 31 N R 14 E S 35 SC B T.

Land, gently rolling.

Soil, clay loam, 2nd rate.

Timber, birch, hemlock, maple, basswood and pine;
undergrowth, young timber.

N. 89° 55' W., along the S. bdy. of Sec. 35.

Over gently rolling land, with heavy timber to
S., and cut-over land, small timber and dense
undergrowth to N.

Enter cedar and birch swamp, bears N. 70° W., and
S. 70° E.

Stream, 5 lks. wide, 6 ins. deep, course S. 25° E.

The true point, for the closing cor. of secs. 5 and
6, after moving 22 lks. N. from its original
position, as determined from an original bearing
tree, in order to place it on the true closing
line.

At point for cor.:

Set a concrete monument, 24 ins. long, 6 ins.
diam., 20 ins. in the ground, for the closing
cor. of secs. 5 and 6, T. 30 N. R. 15 E., with
brass tablet, 3½ ins. diam., 3 in. stem, em-
bedded in top, mkd.

18.70

24.90

35.98

Dependent Resurvey of the Third Standard
Parallel, North, through Range 14, East,
4th Prin. Mer., Wisconsin.

	T31N R14E S35	
	S6 S5 T30 N R15E CC	
	1933	from which
	An original bearing tree:	
	A dead tamarac, 20 ins. diam., bears S. 23° E., 60 lks. dist., with scribe marks.	
	And new bearing trees:	
	A cedar, 8 ins. diam., bears S. 53° E., 49 lks. dist., mkd. T 30 N R 15 E S 5 C C B T.	
	A cedar, 8 ins. diam., bears S. 40½° W., 84 lks. dist., mkd. T 30 N R 15 E S 6 C C B T.	
40.10	Proportionate dist.; there is no remaining evidence of the original post or bearing trees.	
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the standard 1/4 sec. cor., with brass cap mkd.	
	S C	
	1/4 S35	
	1933	from which
	A cedar, 5 ins. diam., bears N. 38° E., 40 lks. dist., mkd, 1/4 S 35 S C B T.	
	A cedar, 5 ins. diam., bears N. 35½° W., 45 lks. dist., mkd, 1/4 S 35 S C B T.	
47.70	Leave swamp, bears N. and S.; thence over gently rolling land.	
80.20	The point for the standard cor. of secs. 34 and 35, as determined from original bearing tree.	
	At point for cor.,	
	Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 34 and 35, with brass tablet, 3½ ins. diam., 3 in. stem, embedded in top, mkd.	

Dependent Resurvey of the Third Standard
Parallel, North, through Range 11, East,
4th Prin. Mer., Wisconsin.

Chains	Remarks
	1933 from which
	Remains of the original bearing trees: A hemlock stub, 18 ins. diam., bears N. 64° E., 46 lks. dist., mkd. R 14 E T 31 N S 35. A hemlock, 20 ins. diam., bears N. 8° W., 29 lks. dist., with marks T 31 N S 34 visible. A hemlock stump, 20 ins. diam., bears N. 65° W., 12 lks. dist. And new bearing trees: A hemlock, 6 ins. diam., bears N. 42° E., 68½ lks. dist., mkd. T 31 N R 14 E S 35 S 4 B T. A hemlock, 12 ins. diam., bears N. 53° W., 14½ lks. dist., mkd. T 31 N R 14 E S 34 S 4 B T. Land, level and rolling. Soil, clay loam on upland, 2nd rate; muck in swamp, 3rd rate. Timber, sugar maple, birch, hemlock, basswood, ironwood and poplar; undergrowth, young timbers.
39.92	S. 89° 19' W., along the S. bdy. of sec. 34. Over heavily rolling land, with heavy timber to S., and cut-over land, and small timber to N. The point for the standard 1¼ sec. cor., which is marked by the hole of the original cor. post, and checked by remains of the original bearing trees. At point for cor., Set in iron post, 3 ft. long, 2 ins. diam., 87 ins. in the ground, for the standard 1¼ sec. post, with brass cap mkd. 1933. Remains of original bearing trees: A rotten balsam stump, bears N. 30° E., 6 lks. dist. A rotten balsam stump, bears N. 10° W., 23 lks. dist. And new bearing trees: A hemlock, 9 ins. diam., bears N. 39° W.

-24-

Dependent Resurvey, of the Third Standard
Parallel, North, through Range 14, East,
4th Prin. Mer., Wisconsin.

Chains	
10.96	23½ lks. dist., mkd. 1/4 S 3/4 S C B T. A yellow birch, 10 ins. diam., bears N. 19½° W., 18 lks. dist., mkd. 1/4 S 3/4 S C B T. N. 89° 43' W., along the S. bdy. of sec. 34. (West half mile. Over gently rolling land. The true point for the closing cor. of Tps 30 N., Rs. 14 and 15 E., after moving 4½ lks. S., from the original point for the cor., as determined from original bearing trees, in order to place it on the true closing line. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the closing cor. of Tp. 30 N., Rs. 14 and 15 E., with brass tablet, 3½ ins. diam., 3 in. stem, embedded in top, mkd, T31N R14E S24 S1 S6 R14 E R15 E T30 N 66
40.16	1933 from which Original bearing trees: A sugar maple stump, 20 ins. diam., bears S. 71½° E., 44 lks. dist., with old blaze opened and marks weathered off, (recorded dist. from original post 6 lks., true dist., 46 lks.) A rock elm, 20 ins. diam., bears S. 81° W., 12 lks. dist., with overgrown blaze. (Tree recorded as maple.) A sugar maple, 20 ins. diam., bears N. 76° W., 11 lks. dist., with scribe marks visible. And new bearing trees: A hemlock, 7 ins. diam., bears S. 24½° W., 52 lks. dist., mkd. T 30 N R 15 E S 60 C B T. A hemlock, 13 ins. diam., bears S. 41½° W., 119 lks. dist., mkd, T 30 N R 14 E S 100 B T, The point for the standard cor. of secs. 33 and 34, as determined from original bearing tree. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 33 and 34, with brass tablet, 3½ ins. diam., 3 in. stem, embedded in top, mkd,

Dependent Resurvey of the Third Standard Parallel, North, through Range 14, East, 4th Prin. Mer., Wisconsin.

Chains	
	S O 731 N R 14 E 833 S 34 1933 from which Remains of original bearing trees: A hemlock stump, 24 ins. diam., bears N. 94° E., 64 lks. dist., with scribe marks visible. A sugar maple, 26 ins. diam., bears N. 84° E., 27 lks. dist., with old blaze opened and scribe marks visible. A stump hole, bears N. 21° W., 18 lks. dist. (Agrees with record for cherry bearing trees). A stump hole, bears N. 23° W., 39 lks. dist. (Agrees with record for elm bearing tree.) And new bearing trees: A hemlock, 10 ins. diam., bears N. 32° E., 34 lks. dist., mcd. T 31 N R 14 E S 34 S C B T. A hemlock, 10 ins. diam., bears N. 79° W., 60 lks. dist., mcd. T 31 N R 14 E S 33 B T. Land, rolling. Soil, clay-loam; 2nd rate. Timber, sugar maple, birch, basswood, hemlock, poplar; undergrowth, young timber.
20.00	N. 89° 47' W., along the S. bdy, of sec, 33, Over-rolling land, with timber to S., and out-over land and young timber to N. Nearly open land, begins to N.
10.16	The point for the standard 1/4 sec. cor., which is marked by a wooden post, 4 x 4 x 30 ins., above ground, set by a local surveyor, from original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard 1/4 sec. cor., with brass tablet, 3 1/2 ins. diam., 3 ins. stem, embedded in top, mcd. S O. 1/4 S 33 1933 from which Remains of the original bearing trees: A hemlock stump, 18 ins. diam., bears N. 81° E., 13 lks. dist., mcd. S T,

Dependent Resurvey of the Third Standard
Parallel, North, through Range 14, East,
4th Prin. Mer., Wisconsin.

Chains	
	A hemlock stump, 20 ins. diam., bears N. 64° W., 33 lks. dist., with overgrown blaze. And new bearing trees: An elm, 8 ins. diam., bears N. 66½° E., 9 lks. dist., mkd. 1/4 S 33 S C B T. No other suitable accessory available.
10.60	S. 89° 56' W., along the S. bdy. of sec. 33. (West half mile.) The true point for the closing cor. of secs. 1 and 2, after moving 2½ lks. N., from the original position of the cor., as determined from an original bearing tree, in order to place the cor. on the true closing line. The tree point for cor., falls on an outcropping rock. At the true point for cor., Mark an x on rock, over which set a concrete monument, 16 ins. long, 6 ins. diam., supported by mound of stone to top, for the closing cor. of secs. 1 and 2, T. 30 N., R. 14 E., with brass tablet, 3½ ins. diam., 3 in. stem, embedded in top, mkd. T31N R14E S2 S33 S1 T30N R14E CC. 1933 from which The remains of an original bearing tree: A birch stump, 30 ins. diam., bears S. 75° E., 22½ lks. dist., with old blaze opened and rotted out. And new bearing trees: A sugar maple, 10 ins. diam., bears S. 28° E., 48 lks. dist., mkd. T 30 N R 14 E S 1 C O B T. A sugar maple, 9 ins. diam., bears S. 35½° W., 68 lks. dist., mkd. T 30 N R 14 E S 2 C C B T. The point for the standard cor. of secs. 32 and 33, which is marked by a wooden post, 3 x 3 x 30 ins. above ground, at cor. of fences bearing E. and W., and N. At point for cor., S C T31N R14E S32 S33 1933 from which
40.15	

Dependent Resurvey of the Third Standard
Parallel, North, through Range 14, East,
4th Principal Mer., Wisconsin.

Chains	Remains of original bearing trees;
	A birch, stump, 26 ins. diam., bears N. 9° E., 49 lks. dist.
	A fallen birch, 14 ins. diam., bears N. 20° W., 36 lks. dist., with old blazes.
	And new bearing trees:
	A hemlock, 9 ins. diam., bears N. 69½° E., 52 lks. dist., mkd. T 31 N R 14 E S 33 80 B T.
	A hemlock, 12 ins. diam., bears N. 77½° W., 169 lks. dist., mkd. T 31 N R 14 E S 32 80 B T.
	Land, rolling. Soil, clay loam, 2nd rate. Timber, sugar, maple, birch, elm, basswood, hemlock, poplar, undergrowth, young timber.
40.14	S. 89° 55' W., along the S. bdy. of Sec. 32. Over rolling land, with heavy timber to S., and out-over land and young timber to N. The point for the standard 1/4 sec. cor., which is marked by an iron pipe, 1½ x 6 ins. above ground, set by a local surveyor from original bearing trees. At point for cor., Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the standard 1/4 sec. cor., with brass cap mkd. S O 1/4 S 32 1933 from which
	Remains of original bearing trees: A hemlock stump, 24 ins. diam., bears N. 39° E., 46 lks. dist., with part of negative of old blaze alongside. A sugar maple stump, 20 ins. diam., bears N. 75° W., 49 lks. dist., with an iron pipe, 3 ins. diam., set in ground alongside as identification. No suitable accessory available.
11.30	N. 89° 57' W., along the S. bdy. of Sec. 32. (West half mile.) Record dist., there is no remaining evidence of the original post or bearing trees of the closing cor. of secs. 2 and 3, Tp. 30 N., R. 14 E.
36.30	Left bank of the north branch of Evergreen River, course S. 10° E.
36.90	Right bank of River.

Dependent Resurvey of the Third Standard
Parallel, North, through Range 11, East,
4th Principal Mer., Wisconsin.

Chains	
40.08	The point for the standard cor. of Secs. 31 and 32, which is marked by a wooden post, 4 x 4 x 30 ins. above ground, set by a local surveyor, from original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 31 and 32, with brass table, 2 1/2 ins. diam., 3 in. stem, embedded in top, mkd., S O TAXN FILED 531 532 1933 From which Remains of original bearing trees: A birch stump, 20 ins. diam., bears N. 64 1/2° E., 104 lks. dist., with overgrown foot blaze. (Record bearing, N. 63° E.) A birch stump, 24 ins. diam., bears N. 46° W., 64 lks. dist., with foot blaze. (Record bearing, N. 47° W.) And new bearing trees: A hemlock, 7 ins. diam., bears N. 81 1/2° E., 102 1/2 lks. dist., mkd. T 31 N R 14 E S 32 SO B T. A hemlock, 8 ins. diam., bears N. 72 1/2° W., 66 lks. dist., mkd. T 31 N R 14 E S 31 SO B T. Land, rolling. Soil, clay loam, 2nd rate. Timber, sugar maple, birch, hemlock, basswood, poplar; undergrowth, young timber.
39.97	N. 89° 49' W., along the S. bdy. of Sec. 31. Over rolling land, with heavy timber to S. and out-crover land and small timber to N. The point for the standard 1/4 sec. cor., as determined from original bearing trees. At point for cor., Set an iron post, 3 ft. long, 6 ins. diam., 27 ins. in the ground, for the standard 1/4 sec. cor., with brass cap mkd., S O 1/4 531 1933 from which Remains of original bearing trees: A sugar maple stump, 30 ins. diam., 9 ft. high, bears N. 15° E., 90 lks. dist., with pop and foot

-29-

Dependent Resurvey of the Third Standard Parallel, North, through Range 14, East, 4th Prin. Mer., Wisconsin.

Chains

blazes opened and marks weathered off and remarked JOC-EJB-BT.

A large stump hole, bears N. 57° E., 56 lks. dist.

And new bearing trees:

A sugar maple, 12 ins. diam., bears N. 55° E., 68 lks. dist., mkd. 1/4 S 31 S C B T.

An elm, 5 ins. diam., bears N. 10° W., 49 1/2 lks. dist., mkd. 1/4 S 31 S C B T.

N. 89° 47' W., along the S. bdy. of sec. 31. (West half mile.)

11.05

The point for the closing cor. of secs. 3, and 4, as determined from original bearing trees.

At point for cor.,

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the closing cor. of secs. 3 and 4, T. 30 N., R. 14 E., with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd.

T31N R14E
S31
S4 S3
T30N R14E
CC

1933 from which

Remains of original bearing trees:

A stump hole, bears S. 3° E., 82 lks. dist. (Agrees with record for basswood bearing tree.)

A basswood stump, 26 ins. diam., bears S. 20° W., 26 lks. dist., with weathered old blaze; the stump has been incorrectly re-marked 1/4 S B T.

And new bearing trees:

A rock elm, 12 ins. diam., bears S. 18 1/2° W., 83 lks. dist., mkd. T 30 N R 14 E S 3 C C B T.

A sugar maple, 7 ins. diam., bears S. 40° W., 63 lks. dist., mkd. T 30 N R 14 E S 4 C C B T.

The point for the standard cor. of Tps. 31. N., Rs. 13 and 14 E., which is marked by wooden post, 3/4 x 3 x 30 ins. above ground, set by a local surveyor from original bearing trees.

At point for cor.,

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of Tps. 31 N., Rs. 13 and 14 E., with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd.

43.16

Dependent Resurvey of the Third Standard Parallel, North, through Range 14, East, 4th Prin. Mer., Wisconsin.

Chains	S C T 31 N R 13 E S 36 S 31	from which
	1933	
	Remains of original bearing trees:	
	A stump hole, bears N. 17° E., 52 lks. dist. (Agrees with record for sugar maple bearing tree.)	
	A dead sugar maple, 20 ins. diam., bears N. 73° W., 6 lks. dist., with old blaze rotted out but definite.	
	And new bearing trees:	
	A hemlock, 8 ins. diam., bears N. 29° E., 118 lks. dist., mkd. T 31 N R 14 E S 31 S C B T.	
	A hemlock, 18 ins. diam., bears N. 44½° W., 118 lks. dist., mkd. T 31 N R 13 E S 36 S C B T.	
	land, rolling.	
	Soil, clay loam; 2nd rate.	
	Timber, sugar maple, birch, hemlock, basswood, poplar and pine; undergrowth, young timber.	
	Dependent Resurvey of the Third Standard Parallel, North, through Range 13, East, as originally surveyed by James Marsh, U. S. Deputy Surveyor, in 1851.	
140.17	N. 89° 48' W., along the S. bdy. of sec. 36, marking and blazing the true line.	
	The point for the standard 1/4 sec. cor., which is marked by a rotted wooden post, set by a local surveyor, B. F. Dorr, of Antigo, Wisconsin, from original bearing trees.	
	At point for cor.,	
	Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard 1/4 sec. cor., with brass cap mkd.	
	S C 1/4 S 36	from which
	1933	
	Remains of original bearing trees:	
	A rotted elm stump, 15 ins. diam., bears N. 70° E., 33 lks. dist.	
	A rotted elm stump, 20 ins. diam., bears N. 55° E., 19 lks. dist.	