

The attached document is a portion 10446 as originally received. The entire original document, when scanned, was too large for most email programs.

Although the 4 four pages of 10446 are very hard to read, they contain background information on these notes and the surveying process.

RECORD # 10225
LANGLADE COUNTY SURVEYORS OFFICE
DATE FILED: 6/1/15 BY: D-THURSTY

-30-

Dependent Resurvey of the Third Standard Parallel, North, through Range 14, East, 4th Prin. Mer., Wisconsin.

Chains	
S C T 31 N R 13 E S 36 S 31	from which
1933	Remains of original bearing trees:
	A stump hole, bears N. 17° E., 52 lks. dist. (Agrees with record for sugar maple bearing tree.)
	A dead sugar maple, 20 ins. diam., bears N. 75° W., 6 lks. dist., with old blaze rotted out but definite.
	And new bearing trees:
	A hemlock, 8 ins. diam., bears N. 29° E., 118 lks. dist., mkd. T 31 N R 14 E S 31 S C B T.
	A hemlock, 48 ins. diam., bears N. 14 1/2° W., 118 lks. dist., mkd. T 31 N R 13 E S 36 S C B T.
	Land, rolling. Soil, clay loam; 2nd rate. Timber, sugar maple, birch, hemlock, basswood, poplar and pine; undergrowth, young timber.
	Dependent Resurvey of the Third Standard Parallel, North, through Range 13, East, as originally Surveyed by James Marsh, U. S. Deputy Surveyor, in 1851.
40.17	N. 89° 48' W., along the S. bdy. of sec. 36, marking and blazing the true line.
	The point for the standard 1/4 sec. cor., which is marked by a rotted wooden post, set by a local surveyor, B. F. Dorr, of Antigo, Wisconsin, from original bearing trees.
	At point for cor.,
	Set an iron post, 3 ft. long, 2 ins. diam., 27 in. in the ground, for standard 1/4 sec. cor., with brass cap mkd.
	S C 1/4 S 36
	1933 from which
	Remains of original bearing trees:
	A rotted elm stump, 15 ins. diam., bears N. 70° E., 33 lks. dist.
	A rotted elm stump, 20 ins. diam., bears N. 35° E., 49 lks. dist.

Dependent Resurvey of the Third Standard Parallel, North, through Range 13, East, 4th Prin. Mer., Wisconsin.

Chains	
	A rotted elm stump, bears N. 81° W. 29 lks. dist. (Record bearing N. 78° W.) And new bearing trees: A sugar maple, 12 ins. diam., bears N. 45° E., 47 lks. dist., mkd. 1/4 S 36 SC B T. A sugar maple, 4 ins. diam., bears N. 68° W., 81 lks. dist., mkd. 1/4 S 36 SC B T.
7.67	N. 89° 45' W., along the S. bdy. of Sec. 36. (West half mile.)
18.90	Record dist.; there is no remaining evidence of the closing cor. of secs. 4 and 5, T. 30 N., R. 14 E.
21.50	Wisconsin and Northern Railroad, bears N. 10° W. and S. 10° E.
40.11	Wagon road, bears N. and S. 30° E. The point for the standard cor. of secs. 35 and 36, as determined from an original bearing tree. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 35 and 36, with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd.
	S C T31N R13E S35 T36
	1933 from which The remains of an original bearing tree: An elm stump, 26 ins. diam., bears N. 40° W., 59 lks. dist.; I uncover foot blaze and negative of letter "T." And new bearing trees: A rock elm, 5 ins. diam., bears N. 64 1/2° E., 53 lks. dist., mkd. T 31 N R 13 E S 36 SC B T. A rock elm, 4 ins. diam., bears N. 48 1/2° W., 33 lks. dist., mkd. T 31 N R 13 E S 35 SC B T. Land, rolling. Soil, clay loam, 2nd rate. Timber, sugar maple, elm, birch, basswood, hemlock and poplar; undergrowth, young timber.
26.30	West, along the S. bdy. of Sec. 35. Over gently rolling land, with heavy timber to S., and out-over land and dense undergrowth to N. Road, bears N. and S.

Dependent Resurvey of the Third Standard
Parallel, North, through Range 13 East,
14th Pine Mer., Wisconsin.

Chains	
40.23	The point for the standard 1/4 sec. cor., as determined from original bearing trees. At point for cor., Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for the standard 1/4 sec. cor., with brass cap mkd. 1/4 S 35 1933 from which Remains of original bearing trees: A birch stump, 18 ins. diam., bears N. 38° E., 43 lks. dist., with part of foot blaze. A birch stump, 24 ins. diam., bears N. 14° E., 66 lks. dist. A stump hole, bears N. 52° W., 47 lks. dist. (Agrees with record for sugar maple bearing tree.) And a new bearing tree. A hemlock, 8 ins. diam., bears N. 87½° E., 78½ lks. dist., mkd. 1/4 S 35 S T. No other suitable accessories available.
7.80	N. 89° 17' W., along the S. bdy. of sec. 35. (West half mile). Record dist.; there is no remaining evidence of the post or bearing trees of the closing cor. of secs. 5 and 6, T. 30 N., R. 14 E.
18.40	Left bank of West Branch of Evergreen River, 60 lks. wide, course S.
22.80	Top of narrow, rocky ridge, bears N. 80° E., and S. 78° W.
30.60	Top of same narrow ridge, bears N. 50° W., and S. 50° E.
32.80	Enter cedar and tamarack swamp, bears N. 20° W., and S. 20° E.
38.10	Creek, 15 lks. wide, 12 ins. deep, course SW. 40 lks., then SE.
39.97	The point for the standard cor. of secs. 34 and 35, as determined from original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 34 and 35, with brass tablet, 3½ ins. diam., 3 in. stem, embedded in top, mkd.

Dependent Resurvey of the Third Standard
 Parallel, North, through Range 13, East,
 34th Prin. Mer., Wisconsin.

Chains	
	S O 1/4 1/4 834 835 1933 from which Remains of original bearing trees: A birch stub, 16 ins. diam., bears N. 7° E., 45 lks. dist., with scribe marks visible. A birch, 16 ins. diam., bears N. 33° W., 34 lks. dist., with scribe marks visible. And new bearing trees: A cedar, 5 ins. diam., bears N. 28 1/2° E., SC B T. 70 1/2 lks. dist., mkd. T 31 N R 13 E S 35 SC B T. A hemlock, 9 ins. diam., bears N. 67 1/2° W., 85 1/2 lks. dist., mkd. T 31 N R 13 E S 34 SC B T. Land, rolling. Soil, clay loam, 2nd rate. Timber, sugar maple, elm, hemlock, birch, basswood, cedar and tamarack; undergrowth, young timber.
0.40	N. 89° 29' W., along the S. bdy. of Sec. 34. Over level land, through cedar swamp. Leave swamp, bears NW. and SE.; thence over rolling land, with heavy timber to S., and cut-over land and undergrowth to N. Enter cedar and tamarack swamp, bears NE. and SW. Creek, 10 lks. wide, 6 ins. deep. sluggish current, course N. 15° E. Leave swamp, bears N. 30° E., and S. 30° W., thence over rolling land. The point for the standard 1/4 sec. cor., as de- termined from original bearing trees. At point for cor.,
10.60	
13.70	
24.30	
40.08	
	S O 1/4 834 1933 from which The remains of original bearing trees: A hemlock stump, 16 ins. diam., bears N. 60° E., 36 lks. dist., with part of foot blaze. A stump hole, bears N. 22° E., 10 lks. dist., (Agrees with record for hemlock bearing tree.)

-34-

Dependent Resurvey of the Third Standard Parallel, North, through Range 13, East, 4th Prin. Mer., Wisconsin.

Chains	No suitable accessory available.	51.710
8.44	N. 89° 49' W., along the S. bdy. of Sec. 34. (West half mile.) The true point for the closing cor. of Tp. 30 N., Rs. 13 and 14 E., after moving 11 lks. N., from the original point for the cor., as determined from original bearing trees, in order to place the cor. on the true closing line. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the closing cor. of Tp. 30 N., Rs. 13 and 14 E., with brass tablet embedded in top, mkd. T31N R13 E S34 S1 S6 R13E R14E T30N CC	
40.10	1933 from which The remains of original bearing trees: A stump hole, and maple roots, bear S. 43° E., 39 lks. dist., (Agrees with record for maple bearing tree.) A dead maple stub, 18 ins. diam., bears S. 8° W., 53 lks. dist., with scribe marks. And new bearing trees: A hemlock, 16 ins. diam., bears S. 24° E., 98 lks. dist., mkd. T 30 N R 14 E S 6 CC B T. A hemlock, 28 ins. diam., bears S. 56° W., 130 lks. dist., mkd. T 30 N R 13 E S 1 CC B T. Proportionate dist.; there is no remaining evidence of the original post or bearing trees. Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 33 and 34, with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd. S. O. T31N R13E S33 S34 1933 from which A local bearing tree: A dead hemlock, 12 ins. diam., bears N. 51 1/2° W., 17 lks. dist., mkd. S 33. No suitable accessory available. Land, level swamp and rolling upland. Soil, muck, 3rd rate, in swamp; clay loam, 2nd rate	

Dependent Resurvey of the Third Standard
Parallel, North, through Range 13, East,
4th Principal Mer., Wisconsin.

Chains	
	on upland. Timber, sugar maple, birch, elm, hemlock, basswood, and poplar; undergrowth, young timber.
	N. 89° 49' W., along the S. bdy. of sec. 33. Over rolling land, with heavy timber to S., and out-over land and undergrowth to N. The point for the standard 1/4 sec. cor. as determined from original bearing trees. At point for cor., Set an iron post, 3 ft. long, 2 ins. diam., 27 ins. in the ground, for standard 1/4 sec. cor., with brass cap mkd. T30N R13E S 0
40.10	1/4 S33 1933 Remains of original bearing trees: A dead hemlock, 28 ins. diam., bears N. 40° W., 22 lks. dist., mkd. R 13 E T 31 N 1/4 S. A stump hole, bears N. 28° E., 53 lks. dist., (agrees with record of birch bearing tree.) No suitable accessory available.
8.64	N. 89° 39' W., along the S. bdy. of Sec. 33. (West half mile.) The true point for the closing cor. of secs. 1 and 2, T. 30 N., R. 13 E., after moving 6 1/2 lks. N. 4 from the original point for the cor., as determined from original bearing trees, in order to place the cor. on the true closing line. At true point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the closing cor. of secs. 1 and 2, T. 30 N., R. 13 E., with brass tablet, 2 1/2 ins. diam., 3 in. stem, embedded in top, mkd. T31N R13E S33 S2/S1 T30N R13E CO 1933 from which Remains of original bearing trees: A fallen hemlock, 16 ins. diam., bears S. 11 1/2° E., 46 1/2 lks. dist., with old plate opened.

Independent Resurvey of the Third Standard
Parallel, North, through Range 13, East,
14th Prin. Mer., Wisconsin.

Chains	
	A fallen hemlock, 14 ins. diam., bears S. 50$\frac{1}{2}$° E., 48 lks. dist., with old blaze opened. And new bearing trees: A hemlock, 12 ins. diam., bears S. 28$\frac{1}{2}$° E., 102 lks. dist., mkd. T 36 N R 13 E S 1 CC B T. A hemlock, 12 ins. diam., bears S. 41$\frac{1}{2}$° W., 129 lks. dist., mkd. T 30 N R 13 E S 2 CC B T. E. shore of pond, on West Branch of Wolf River, bears N. 15° W., and S. 15° E. W. shore of pond, bears N. 10° W. and S. 20° E.; thence over rolling land. The point for the standard cor. of secs. 32 and 33, as determined from original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for standard cor. of secs. 32 and 33, with brass tablet, 3$\frac{1}{2}$ ins. diam., 3 in. stem, embedded in top, mkd. S O T 31 N R 13 E 832 833 1933 Remains of original bearing trees: A hemlock stump, 14 ins. diam., bears N. 38° E., 54 lks. dist. A hemlock, 12 ins. diam., bears N. 71° W., 26 lks. dist., with overgrown blazes. A local bearing tree: A sugar maple, 18 ins. diam., bears S. 62$\frac{1}{2}$° E., 19 lks. dist., mkd. B T. And a new bearing tree: A basswood, 4 ins. diam., bears N. 45° E., 52 lks. dist., mkd. T 31 N R 13 E S 33 SO B T. Land, rolling. Soil, clay loam, 2nd rate. Timber, hemlock, sugar maple, birch, elm, basswood, and oak; undergrowth, young timber.
29.85	
33.50	
39.94	
40.08	N. 89° 47' W., along the S. bdy. of sec. 32. Over rolling land, with heavy timber to S., and cut-over land and undergrowth to N. The point for the standard 1/4 sec. cor., which is mkd. by a wooden post, 4 x 4 x 36, ins. above ground, set by a local surveyor from original bearing trees. At point for cor.,

Dependent Resurvey of the Third Standard
Paramet., North, through Range 13, East,
4th Prin. Mer., Wisconsin.

Chains.	Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard 1/4 sec. cor., with brass tablet, 3/4 ins. diam., 3 in. stem, embedded in top, mkd.
	1/4 S 32 1933 from which
	Remains of original bearing trees:
	A fallen sugar maple, 18 ins. diam., bears N. 50° W., 19 lks. dist., with old blaze.
	A stump hole, bears N. 10° W., 25 lks. dist. (Agrees with record for a hemlock bearing tree.)
	A local bearing tree:
	A hemlock, 16 ins. diam., bears S., 5 lks. dist., mkd. 1/4 S B T.
	And new bearing trees:
	A hemlock, 10 ins. diam., bears N. 38° E., 48 lks. dist., mkd. 1/4 S 22 80 B T.
	A birch, 4 ins. diam., mkd. on bark 1/4 S 32 80 B T.
10.18	N. 89° 46' W., along the S. bdy. of sec. 32, (West half mile.)
	The true point for the closing cor. of secs. 2 and 3, T. 30 N., R. 13 E., after moving 6 1/2 lks. N. from the original point for the cor., as determined from original bearing trees, in order to place it on the true closing line.
	At the true point for cor.,
	Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for closing cor. of secs. 2 and 3, T. 30 N., R. 13 E., with brass tablet, 3/4 ins. diam., 3 in. stem, embedded in top, mkd.
	T31N R13E S32 T30N R13E CC
	1933 from which
	Remains of original bearing trees:
	A rotted hemlock stump, bears S. 73° E., 48 lks. dist., with marks 30 R13E 2 visible.
	A rotted sugar maple stump, bears S. 35° E., 32 lks. dist., with old blaze.
	A fallen hemlock, 10 ins. diam., bears S. 44° W., 48 lks. dist., mkd. T 30 N R 13 E S 3,
	And new bearing trees:

Dependent Resurvey of the Third Standard
Parallel, North, through Range 13, East,
4th Prin. Mer., Wisconsin.

Chains.	
	A hemlock, 12 ins. diam., bears S. 21$\frac{1}{2}$° E., 28 lks. dist., mkd., T 30 N R 13 E S 2 CC B T. A sugar maple, 8 ins. diam., bears N. 46$\frac{1}{2}$° W., 21 lks. dist., mkd. T 30 N R 13 E S 3 CC B T. The point for the standard cor. of secs. 31 and 32, as determined from original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 31 and 32, with brass tablet, 24 ins. diam., 3 in. stem, embedded in top, mkd. S C T 31 N R 13 E S 31 S 32 1933 from which Remains of original bearing trees: A stump hole, bears North, 32 lks. dist., (agrees with record for hemlock bearing tree.) A stump hole, bears N. 79° E., 46 lks. dist., (agrees with record for a sugar maple bearing tree.) A birch, 26 ins. diam., bears N. 33$\frac{1}{2}$° W., 25 lks. dist., with old blaze open. (Record bearing N. 38° W.) A local bearing tree: A hemlock, 20 ins. diam., bears S. 46$\frac{1}{2}$° E., 18 lks. dist., mkd. B T. And new bearing trees: A sugar maple, 4 ins. diam., bears N. 71$\frac{1}{2}$° E., 36 lks. dist., mkd. T 31 N R 13 E S 32 SO B T. A hemlock, 15 ins. diam., bears N. 78$\frac{1}{2}$° W., 175 lks. dist., mkd. T 31 N R 13 E S 31 SO B T. Land, rolling! Soil, clay loam, 2nd rate. Timber, sugar maple, birch, hemlock, basswood and poplar; undergrowth, young timber.
40.54	
	N. 89° 43' W., along the S. bdy. of sec. 31, Over rolling land, with heavy timber to S, and out- over land and undergrowth to N. Proportionate dist., there is no remaining evidence of the original post or bearing trees. Set a concrete monument, 24 ins. long, 6 ins. diam., 20 in. in the ground, for the standard 1/4 sec. cor., with brass tablet, 24 ins. diam., 3 in. stem, embedded in top, mkd.
40.02	

Dependent Resurvey of the Third Standard
Parallel, North, through Range 13, East,
4th Prin. Mer., Wisconsin.

Chains.		
	S C 1/4 S 31 1933	from which
		A hemlock, 10 ins. diam., bears N. 85° E., 175 lks. dist., mkd. 1/4 S 31 S C B T.
		A hemlock, 8 ins. diam., bears N. 35° W., 104 lks. dist., mkd. 1/4 S 31 S C B T.
49.18		Record dist.; there is no remaining evidence of the original post or bearing trees of the closing cor. of secs. 3 and 4.
50.00		E. shore of flooded marsh, bears N. and S.
52.00		W. shore of flooded marsh, bears N. and S.
66.50		Enter cedar and tamarack swamp, bears N. 30° W., and S. 30° E.
66.70		Creek, 30 lks. wide, 2 ft. deep, current sluggish, S C B T.
70.00		E. shore of spring hole.
71.50		W. shore of spring hole.
74.00		Leave swamp, bears NW. and SE.; thence over rolling land.
83.04		The point for the standard cor. of Tp. 31 N., Rs. 12 and 13 E., which is marked by a wooden post, 4 x 4 x 30 ins. above ground, set by a local surveyor for original bearing trees.
		At point for cor.,
		Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of Tp. 31 N., Rs. 12 and 13 E., with brass tablet, 3 x 4 diam., 3 in. stem, embedded in top, mkd.
	S C T 31 N R 12 E R 13 E S 36 S 31 1933	from which
		Remains of original bearing trees:
		A rotted maple stump, bears N. 58° E., 33 lks. dist.
		A stump hole, bears N. 35° E., 7 lks. dist., (agrees with record for sugar maple bearing tree.)
		Hemlock roots, bear N. 17° W., 35 lks. dist.
		A local bearing tree:
		A sugar maple, 16 ins. diam., bears S. 73½° E., 53 lks. dist., mkd. B T.
		And new bearing trees:

Dependent Resurvey of the Third Standard Parallel, North, through Range 13, East, 4th Prime Mer., Wisconsin.

Chains	
	A sugar maple, 12 ins. diam., bears N. 82½° E., 145 lks. dist., mkd. T 31 N R 13 E S 31 S C B T. A white oak, 18 ins. diam., bears N. 27½° W., 272 lks. dist., mkd. T 31 N R 12 E S 36 S C B T. Land, rolling. Soil, East 1/2, clay loam, 2nd rate; West 1/2, sandy, 3rd rate. Timber, hemlock, sugar maple, birch, basswood, poplar and pine; undergrowth, young timber.
	Dependent Resurvey of a Portion of the Third Parallel, North, through Range 12, East, as Surveyed Originally by James M. Marsh, U. S. Deputy Surveyor, in 1851.
2.40	N. 89° 43' W., along the S. bdy. of sec. 36, marking and blazing the true line.
9.30	Over heavily rolling land, through very scattering timber and undergrowth.
40.01	Enter open marsh, bears N. and S.
	Leave marsh, bears N. 30° W., and S. 30° E.; enter heavy timber.
	The point for the standard 1/4 sec. cor., which is marked by a wooden post, 4 x 4 x 30 ins., above ground, set by a local surveyor from original bearing trees:
	At point for cor.,
	Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard 1/4 sec. cor., with brass tablet embedded in top, mkd.,
	80
	1/4 S 36
	1933 from which
	Remains of original bearing trees:
	A rotted elm stump, 16 ins. diam., bears N. 15° E., 12 lks. dist.
	A sugar maple, stump, 20 ins. diam., bears N. 34° W., 61 lks. dist., with foot blaze.
	And new bearing trees:
	A hemlock, diameter not recorded, bears N. 50° E., 45 lbs. dist., mkd. 1/4 S 36 S C B T.
	A hemlock, 10 ins. diam., bears N. 51½° W., 57 lks. dist., mkd. 1/4 S 36 S C B T.