

The attached document is a portion 10446 as originally received. The entire original document, when scanned, was too large for most email programs.

Although the 4 four pages of 10446 are very hard to read, they contain background information on these notes and the surveying process.

RECORD # 10226
LANGLADE COUNTY SURVEYORS OFFICE
DATE FILED: 6/1/15 BY: D. TRUSTY

Dependent Resurvey of the Third Standard Parallel, North, through Range 13, East, 4th Prin. Mer., Wisconsin.

Chains

A sugar maple, 12 ins. diam., bears N. 82½° E., 145 lks. dist., mkd. T 31 N R 13 S 31 S C B T.

A white oak, 18 ins. diam., bears N. 27½° W., 272 lks. dist., mkd. T 31 N R 12 E S 36 S C B T.

Land, rolling.

Soil, East 1/2, clay loam, 2nd rate; West 1/2, sandy, 3rd rate.

Timber, hemlock, sugar maple, birch, basswood, poplar and pine; undergrowth, young timber.

Dependent Resurvey of a Portion of the Third Parallel, North, through Range 12, East, as Surveyed Originally by James M. Marsh, U. S. Deputy Surveyor, in 1851.

N. 89° 43' W., along the S. bdy. of sec. 36, marking and blazing the true line.

Over heavily rolling land, through very scattering timber and undergrowth.

Enter open marsh, bears N. and S.

Leave marsh, bears N. 30° W., and S. 30° E.; enter heavy timber.

The point for the standard 1/4 sec. cor., which is marked by a wooden post, 4 x 4 x 30 ins. above ground, set by a local surveyor from original bearing trees!

At point for cor.,

Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard 1/4 sec. cpr., with brass tablet embedded in top, mkd.,

80

1/4. 836

1933 from which

Remains of original bearing trees:

A rotted elm stump, 16 ins. diam., bears N. 15° E., 12 lks. dist.

A sugar maple, stump, 20 ins. diam., bears N. 34° W., 61 lks. dist., with foot blade.

And new bearing trees:

A hemlock, diameter not recorded, bears N. 30° E., 15 lks. dist., mkd. 1/4 S 36 S C B T.

A hemlock, 10 ins. diam., bears N. 51½° W., 57 lks. dist., mkd. 1/4 S 36 S C B T.

Dependent Resurvey of a Portion of the Third
Parallel, North, through Range 12, East,
4th Prin. Mer., Wisconsin.

Chains	
6.48	N. 89° 44' W., along the S. bdy. of sec. 36. (West half mile.) The point for the closing cor. of secs. 4 and 5, as determined from the original bearing trees. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the closing cor. of secs. 4 and 5, T. 30 N., R. 13 E., with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd.
	T31N R12E S36 S4 T30N R13E C6 from which
	Remains of original bearing trees: A fallen and rotted sugar maple, bears S. 31° E., 4 1/2 lks. dist. A hollow basswood, 18 ins. diam., bears S. 21° W., 51 lks. dist., with part of foot blaze visible. And new bearing trees:
20.00	Field begins to N. of line, edge bears N.
39.86	Leave field, enter lane, bears N.
40.06	The point for the standard cor. of secs. 35 and 36, as determined from an original bearing tree. At point for cor., Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard cor. of secs. 35 and 36, with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd., T31N R12E S35 S36 T30N R13E C6 from which
	Remains of an original bearing tree: A sugar maple stump, 20 ins. diam., bears N. 20° W., 4 1/2 lks. dist., with old foot blaze. And new bearing trees: An elm, 4 ins. diam., bears N. 17° E., 69 1/2 lks. dist., mkd. S 36 S C B T. An elm, 14 ins. diam., bears N. 49 1/2° W., 266 lks. dist., mkd. T 31 N R 13 E S 35 S C B T.
	The cor. falls at E. side of old fence, 12 lks. N. of new cor. post of fence bearing N. and S.

Dependent Resurvey of a Portion of the Third
Parallel, North, through Range 12, East,
4th Prin. Mer., Wisconsin.

Chains	
	Land, rolling. Soil, clay loam, 2nd rate. Timber, sugar maple, birch, hemlock, basswood, elm, poplar; undergrowth, young timber.
	S. 89° 54' W., along the S. bdy. of sec. 35. Over rolling land, with heavy timber to S., and newly cleared land to N. Enter cedar and alder swamp, bears N. and SW. E. bank of a channel of Little West Branch of Wolf River, course S. W. bank of channel, thence over island. E. bank of W. channel of Little West Branch of Wolf River, course S. W. bank of channel. Leave swamp; thence over rolling land through heavy timber. Proportionate dist.; there is no remaining evidence of the original post or bearing trees. Set a concrete monument, 24 ins. long, 6 ins. diam., 20 ins. in the ground, for the standard 1/4 sec. cor. of sec. 35, with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd. S C 1/4 835 1933 from which A sugar maple, 12 ins. diam., bears N. 33 1/2° E., 17 lks. dist., mkd. 1/4 S 35 S O B T. A birch, 16 ins. diam., bears N. 82 1/2° W., 75 lks. dist., mkd. 1/4 S 35 S O B T. Record distance from standard 1/4 sec. cor.; there is no remaining evidence of the original post or bearing trees of the closing cor. of secs. 5 and 6, T. 30 N., R. 13 E. Fence, bears N. and S.; end of timber to N. of line; thence along, or near, S. side of field. Enter road, bears N. and W. House, bears N. 1.50 chs. dist. Proportionate dist.; there is no remaining evidence of the original post or bearing trees. Set a concrete monument, 24 ins. long, 6 ins. diam., 30 ins. in the ground, in road, for the standard cor. of secs. 24 and 35, with brass tablet, 3 1/2 ins. diam., 3 in. stem, embedded in top, mkd.
23.50	
25.80	
26.40	
26.85	
27.85	
30.20	
40.08	
46.70	
52.20	
78.20	
79.00	
80.16	

Dependent Resurvey of a Portion of the Third
Parallel, North, through Range 12, East,
4th Prin. Mer., Wisconsin.

Chains	S C		from which
	T31N S34	R12E S35	
	1933		
	A sugar maple, 14 ins. diam., bears N. 61° W., 105 1/2 lks. dist., mkd. T 31 N R 12 E S 34 S C B T.		
	No other suitable accessory available.		
	Land, rolling.		
	Soil, clay loam, 2nd rate.		
	Timber, sugar maple, birch, hemlock, basswood, elm, poplar and pine; undergrowth, young timber.		
	S. 89° 54' W., along the S. bdy. of sec. 34.		
	Over rolling land, along road.		
18.00	Leave road, bears E. and S. 70° W.; enter timber and undergrowth.		
26.00	Reenter road, bears W. and S. 60° E.		
40.08	A point at proportionate distance for meridional position and in middle of right of way of road bearing E. and W.; for latitudinal position.		
	Set a concrete monument, 24 ins. long, 6 ins. diam., 30 ins. in the ground, on the S. side of the road, for the standard 1/4 sec. cor. of sec. 34, with brass tablet, 3 1/4 ins. diam., 3 in. stem, embedded in top, mkd. S Q		
	1/4 S34		from which
	1933		
	A sugar maple, 16 ins. diam., bears N. 15 1/2° E., 63 lks. dist., mkd. 1/4 S 34 S C B T.		
	A sugar maple, 10 ins. diam., bears N. 43 1/2° W., 101 lks. dist., mkd. 1/4 S 34 S C B T.		
	N. 89° 53' W., on S. bdy. of sec. 34. (W. half mile)		
1.63	The true point for the closing cor. of Tp. 30 N., Rs. 12 and 13 E., after moving 3 lks. N. of the original position as determined from an original bearing tree, in order to place it on the true closing line.		
	At true point for cor.		
	Set a concrete monument, in form of frustum of cone, 24 ins. long, base 12 ins. diam., top 8 ins. diam., 32 ins. in the ground, at intersection of roads, bearing E. and W. and S. for the closing cor. of Tp. 30 N., Rs. 12 and 13 E., with brass tablet, 3 1/4 ins. diam., 3 in. stem, embedded in top, mkd.		

Dependent Resurvey of a Portion of the Third
Parallel, North, through Range 12, East,
4th Prin. Mer., Wisconsin.

Chains

T31N R12 E
S34

S1 S6
R12E R13E
T30N
CC

1933 from which

The remains of an original bearing tree:

A birch stump hole and roots, bears S. 58° E.,
32½ lks. dist. This stump hole was pointed
out by Ed Hanke, a nearby resident, as the
stump of the original bearing tree recorded
as being S. 63° E., 31 lks. dist. from the cor.
Mr. Hanke stated that he had seen scribe
marks on the tree before it was cut.

And a new bearing tree:

A sugar maple, 14 ins. diam., bears S. 51° E.,
66 lks. dist., mkd. T 30 N R 13 E S 66 C C B T.

No other suitable accessory available.

40.08

The point for the standard cor. of secs. 33 and
34, which is marked by a stone, 6 x 8 x 24 ins., set
20 ins. in the ground, at the intersection of roads
bearing E. and W. and N., marked with — on top.
This cor. was perpetuated in 1901, from an original
bearing tree, by E. F. Dorr, a local surveyor.

At a point 36 lks. South of the true point for cor.

Set a concrete monument, 24 ins. long, 6 ins. diam.,
20 ins. in the ground, for witness cor. to the
standard cor. of secs. 33 and 34, with brass tablet,
3½ ins. diam., 3 in. stem, embedded in top, mkd.

W C
S C

T31N R12E
S34 S6
1933

No suitable accessory available.

Land, rolling.
Soil, clay loam, 2nd rate.
Timber, sugar maple, birch, elm, hemlock, poplar,
and pine; undergrowth, young timber.

Dependent Resurvey of the East Boundary
of T. 28 N., R. 16 E., as originally
surveyed by A. G. Ellis, U.S. Deputy
Surveyor, in 1845.

The point for the cor. of Tps. 27 and 28 N., Rs.
16 and 17 E., falls at the intersection of a road
bearing S., and N. 30° E. and old fence lines
bearing E. and W. This point is described by
Mr. J. J. Melendy, of Shawano, Wisconsin,
former County Surveyor, as having been perpetuated
from original evidence.