

LANGLADE COUNTY

SECTION INFORMATION SHEET

BY: Dave Hunt

DATE: 9/23/97

SECTION 20, T. 31 N., R. 12 E.

589°12'16"E 2607.37' N 1/4 COR
1" x 30" IP W/2 ALUM SET
1" x 30" IP W/2 CAP SET 588°54'15"E 2631.59' SEC COR RR SPIKE FOUND

NAIL SET
NAIL FOUND
RR SPIKE SET
RR SPIKE FOUND
IRON PIPE SET (SIZE _____)
IRON PIPE FOUND (SIZE _____)

From Field Work
1997 & 98
8/27/98 D.T.

IT WILL BE ASSUMED THAT ALL DIMENSIONS SHOWN ARE COMPUTED DIMENSIONS, UNLESS THEY ARE MARKED: "(D)" WHICH STANDS FOR DIRECT MEASUREMENT.

FOR US TO USE THE DIRECT MEASUREMENTS IN A LEAST SQUARES ADJUSTMENT, PLEASE COMPLETE THE FOLLOWING:

THEODOLITE ACCURACY _____
MANUFACTURERS EDM ACCURACY _____
SPECIFICATION +—_____mm +—_____ppm

TRAVERSE TARGETS (CIRCLE ONE)
ON TRIBRACHS HANDHELD BOTH

DIRECT ANGLES WERE TURNED _____ TIMES

DIRECT DISTANCES WERE MEASURED (CIRCLE ONE): ONE DIRECTION TWO DIRECTIONS

COMMENTS:

4/26/01 D.T. DETERMINED THAT RR SPIKE FND (PT 43) @ SW COR IS 'BEST EVIDENCE' UNTIL ROAD CAN BE DUG.

64 TO RR SPIKE FND (43)
N78°25'41"W 3.86'

N1°24'35"E 2621.35'

N2°04'53"E 2632.84'

43-64-SECTION LINE:
448° N2°09'51"E
2632.20'

64 PK FND NOT VERIFIED
43 RR SPIKE FND SEC COR

43-111 (SECTION LINE):
S88°32'48"E 2639.66'

N1°24'09"E 2574.18'

21-111 51°27'48"W 2709.09
21-35 51°30'45"W 2706.05

1/4 CON STONE FOUND
S88°28'29"W 2629.59'

35 FND RR SPIKE NOT VERIFIED!

RECORD # 10245
LANGLADE COUNTY SURVEYORS OFFICE
DATE FILED: 8/27/98 BY: D.T.

51°05'02"W 2631.18'
101 1/4 COR
1" x 30" IP W/4 BC SET

51°05'52"W 2632.56'

110 SECTION FROM TIES

30-11	30-12	31-8	31-9	31-10	31-11	31-12	31-13	31-14	31-15	32-8	32-9	32-10	32-11	32-12	32-13	32-14	33-9	33-10	33-11	33-12	33-14	34-9	34-10	34-11	34-12
-------	-------	------	------	-------	-------	-------	-------	-------	-------	------	------	-------	-------	-------	-------	-------	------	-------	-------	-------	-------	------	-------	-------	-------