

INDEX

for

T.33 N. R.10 E.

6	22	5	17	4	13	3	2	1
22	22	21	16	15	14	8	4	
7	21	8	14	9	12	10	11	12
21	20	20	16	15	11	7	3	2
13	17	15	16	14	15	6	14	2
19	19	18	15	14	10	6	2	13
19	18	20	14	21	22	5	23	24
18	17	13	9	5	1			
30	29	28	27	26	25			
31	32	33	34	35	36			

RECORD #

10746

LANOLADE COUNTY SURVEYORS OFFICE

DATE FILED: 12/14/06 BY: JOT/LSY

Notice.

The True Bearing for each distance appears below the heading for each distance. The Magnetic bearing for each distance can be calculated by taking the True Bearing for that particular distance, and in Northeast and Southwest Quadrants subtract it from the Average Declination of 2 - 30 E. For Magnetic Bearings in the Northwest or Southeast Quadrants add the True Bearing to the Average Declination.

In all cases the vernier for magnetic courses is set at zero.

**SUBDIVISION of North Twenty
Four (24) Sections of T 33 N
Range 10 E.**

West Bet. Sec. 24 - 25

Bearing: S 85 - 53 W

4.00 Chs. Along fence and enter Swp.
8.00 " Logging road NW & SE
16.00 " Leave Cedar Swp.
21.26 " Set E 1/16 Cor. Found old
iron pipe, & leave fence.
31.00 " Enter Alder swp.
37.00 " Leave swp. for clearing.
41.50 " Enter small swp.
42.52 " To 1/4 Cor. Galv. iron pipe,
by Co. Surveyor.

Bearing: N 85 - 12 W

1.00 " Leave swp.
3.50 " To private road N & S
9.50 " Enter open swp.
11.50 " Leave swp.
20.33 " Enter W ~~right~~ bottom
21.50 " Enter creek bottom.
22.00 " Creek 15 lks. wide flows SE.
23.50 " To ridge Aspen & W. Birch.
26.50 " Enter swp.
35.50 " Leave swp.
37.00 " Enter swp.
40.66 " To Sec. Cor. 24-25-26-23
Galv. iron pipe by Co.
Surveyor. old B.T.
Spruce 6 N 34 E 118.6 lks.
Spruce 6 S 65 W 101.3 "
Tan. 6 N 23 W 55.9 "

North Bet. Sec. 23 - 24.

Bearing: N 4 - 25 E.

14.40 " Leave swp. for Aspen ridge.
16.40 " Over ridge into Bogus Marsh.
20.61 " Set S 1/16 Cor. in Swp.
41.22 " To old 1/4 Cor. Plain Stake in
swp. Set Tan. post 6 N 45 E
7.1 lks. Tan. post 6 S 45 W
6.5 lks.

Bearing: N 0 - 58 E

18.80 " Through swp. to creek flows SE
20.80 " Set N 1/16 Cor. & leave swp.
41.60 " Through Aspen to Sec. Cor.
13-24-23-14. Found old stake
and ~~old~~ ~~line~~ ~~stake~~ NW.

West Bet. Sec. 13 - 24

Bearing: N 88 - 23 W

Obs.

- 20.475 " Through clearing and along
road and set E 1/16 Cor.
40.95 " Through second growth Huds.
and along road to 1/2 Cor.
Found iron pin for Cor. No
B.T. Set Brass Cap.

Bearing: N 89 - 37 W

- 6.00 " Enter open marsh.
11.00 " Leave marsh for Aspen ridge.
20.82 " Set W 1/16 Cor.
23.00 " Enter open swp.
25.00 " Leave swp.
28.00 " Enter open swp.
31.00 " Leave swp.
41.64 " To Sec. Cor. 13-24-23-14, on
East side of old road.

North Bet. Sec. 13 - 14.

Bearing: N 1 - 26 E.

- 20.135 " Distance to S 1/16 Cor. Did
not set this cor.
31.00 " To South edge of Lake Alta.
33.00 " Over lake.
36.00 " Enter open marsh.
40.27 " To 1/2 Cor. Found old stake in
Swp. but not marked and blazed
W. Pine stp. Due N 103 lks.
New Pine snag N 17 E 104.1 lks.

Bearing: N 6 - 38 E.

- 1.00 " Leave Swp. for Aspen.
18.25 " Enter West edge of Swp.
19.365 " Set N 1/16 Cor. and found old
stake very close to the new one.
20.50 " Leave swp.
25.95 " Cross Town road SW & NE.
38.73 " Along fence to Sec. Cor.
12-13-14-11. Galv. iron pipe
by Co. Surveyor, in old fence
Cor. N - S & W.

West Bet. Sec. 12 - 13.

Bearing: S 89 - 14 W

- 1.00 " To US. Highway 45.
2.00 " Enter open swp.
8.00 " Leave swp.
11.80 " To fence SW & NE and enter swp.
19.50 " Leave swp.

West Bet. Sec. 12 -13 Cont.

20.515 ^{Chs.} " Set East 1/16 Cor. Clearing
North of the line.
38.95 " Fence N & S.
41.03 " To 1/4 Cor. Galv. iron pipe by
Co. Surveyor. This Cor. Set
on prop. before but we find
it to be 12 lks too far West
and 4 lks. too far North.

Bearing: S 89 - 06 W.

20.395 " Set W 1/16 Cor. End of clearing
to the South.
30.00 " Cross town road N & S.
40.79 " To Sec. Cor. 12-13-14-11.

North Bet. Sec. 11 - 12.

Bearing: N 0 09 W.

15.96 " Along fence to S.M.C. on
Greater Bass Lake. Orig. W.
Pine 6 S 25 W 8 lks. Found 2"
iron pipe with cap.

Bearing: N 0 - 13 W

13.00 " Over lake to point of land
14.66 " To 1/4 Cor. Set by Co. Surveyor,
on prop. bet. M.C. Corn. Not
Govt. Very poor in alignment.
His old Pine 30 S 61 E 12 1/2 lks.
still there.

Bearing: N 1 - 14 E.

2.00 " Leave point for lake.
7.59 " To M.C. on North side of lake.
Galv. iron pipe By Co. Surveyor.

Bearing: N 0 - 25 E.

25.00 " Along road to swp. Road turns
NE.
30.00 " Leave swp. and enter road.
38.22 " To Sec. Cor. 1-12-11-2.
Galv. iron pipe in road.
No. B.T. old or new.
Set W.C. 30 lks. West.

West Bet. Sec. 1 - 12

Bearing: S 78 - 14 W.

- Obs.
19.675 " Along C.T.H. "T" and Set E.
1/16 Cor. which falls on South
side of road.
23.00 " C.T.H. "T" turns South.
25.00 " Cross C & NW RR, tracks.
26.15 " To US. highway 45
39.35 " To old 1/2 Cor. Found old
Hem. 11 S 41 1/2 E 12 lks.
New Maple 6 S 41 W 17.8 lks.

Bearing: N 86 - 00 W.

- 17.78 " Through mixed Hwds. To M.C.
on East side of Greater Bass
Lake. Found iron pin with 1-
large mound of rock at base,
which is the end of the lake
platting from the South.

Bearing: N 86 - 01 W.

- 19.80 " Over lake to West shore, but
Could not find any M.C. here.
21.59 " To Sec. Cor. 1-12-11-2.

North Bet. Sec. 1 - 2.

Bearing: N 19 - 30 W.

- 20.24 " Along town road and set S 1/16
Cor. which agrees with old
fence to the West.
40.00 " To center of East & West road.
40.48 " To old 1/2 Cor. Found Limestone
4x4x28 at this Cor. No B.T.
Set W.C. 1 lk. North.

Bearing: N 4 - 33 E.

- 6.50 " Along East edge of Cemetery
to lake.
20.62 " Distance to N 1/16 Cor. in
lake.
26.65 " Over lake.
40.44 " Through Village platting to
Sec. Cor. 36-1-2-35 on North
Town Line.

West Bet. Sec. 25 - 26.

Bearing: S 82 - 41 W

1.00 Obs. Leave swp. for Aspen ridge.
5.10 " Enter Swp. (Aspen Spruce)
12.10 " Leave swp. for Aspen ridge.
14.00 ~~Exit~~ Enter swp.
17.40 " Leave swp.
20.39 1/2 " Set E 1/16 Cor. on top of
high ridge.
22.00 " Enter on East shore of Crooked
Lake, Swp. shore line.
32.00 " Over lake and enter old burnings.
38.385 " To W.C. on East shore of Squaw
Lake Set by Government Surveyors
about 1930. There B.T.
W. Pine 7 N 52 E 52.9 lks.
Spruce 6 S 65 W 109.5 "
40.785 " Distance to 1/2 Cor. in lake.
43.40 " Over Squaw lake, and enter
rough ground.
61.16 1/2 " Set W 1/16 Cor.
68.40 " Enter small Spruce & Tam. swp.
72.40 " Leave swp.
81.57 " To Sec. Cor. 23-26-27-22, Galv.
iron pipe by Co. Surveyor. Old
Sugar 12 N 22 W 56 lks.

North Bet. Sec. 22 - 23.

Bearing: N 1 - 36 E.

10.00 " Enter burned swp.
11.00 " To South shore of lake
name not known, approx. 20 acres
17.00 " To North shore of lake.
19.23 " Set S 1/16 Cor.
37.50 " Enter small Spruce swp.
38.46 " Set 1/2 Cor. on prop.
Tam. post 6 N 45 E 7 lks
Tam. " 6 S 45 W 7.6 "
39.50 " Leave swp. for high ridge
Covered with Aspen & W. Birch.
45.00 " Enter Large Spruce & Tam. Swp.
known as Bogus Marsh.
57.69 " Set N 1/16 Cor. in swp.
76.92 " To Sec. Cor. 14-23-22-15, set
on prop. No evidence of any
Govt. Cor. New B.T.
Tam. 8 S 58 W 72 lks.
Tam. 8 S 12 E 107.2 "
Tam. 8 N 38 E 110.8 "

West Bet. Sec. 14 - 23.

Bearing: S 78 - 46 W.

- 17.85 Chs. Through Aspen & W. Birch
to East side of Bogus Marsh.
21.055 " Distance to E 1/16 Cor. D14
not set.
42.11 " And Set $\frac{1}{2}$ Cor.
Tan. post 7 N 45 E 10 lks.
Tan. " 6 S 45 W 10 "
47.00 " To island in swp. Covered
with Balsam Hem.
50.00 " Over island, into open swp.
78.00 " Enter dense growth of
Spruce and Tan.
84.22 " To Sec. Cor. 14-23-22-15.

North Bet. Sec. 14 - 15.

Bearing: N 2 - 58 E

- 15.60 " Cross old logging road NE & SW
25.50 " Cross stream 20 lks wide
and flows SE., and leave swp.
36.30 " Cross town road runs E & W.
38.51 " To $\frac{1}{2}$ Cor. by Co. Surveyor.
Galv. iron pipe. Old B.T.
Pine Stp. 18 N 71 $\frac{1}{2}$ W 102 lks.
Knife work.

Bearing: N 3 - 12 E

- Enter Swp. at once.
2.50 " Cross stream flows West
10 lks wide.
5.50 " Leave swp.
6.66 " To iron pipe set for lake
platting.
9.51 " To Another iron pipe.
15.20 " To South edge of small pond
19.10 " Over pond.
22.10 " To road E & W. (logging road)
22.97 " To N 1/16 Cor.
33.35 " To old logging road SW & NE.
39.60 " Cross old logging road NW & SE.
45.94 " To Sec. Cor. 11-14-15-10.
Found Old stake and B.T.
Hem. Stp. 10 S 27 W 25.1 lks.
New: Lind. 12 S 87 $\frac{1}{2}$ E 43.6 "
Birch 14 N 11 W 46.4 "

West Bet. Sec. 11 - 14.

Bearing: S 86 - 19 W.

21.27 Chs. Along fence and set E 1/16 Cor
Fence to the North.
23.50 " Cross old RR. grade NE & SW.
26.00 " Enter clearing.
42.54 " To Town road and the 1/4 Cor.
Set this 1/4 Cor. from E 1/16
Cor. and found it O.K.
Set W.C. 40 lks West.

Bearing: S 88 - 56 W.

00.40 " To W.C. To 1/4 cor.
2.37 " To W.C. to M.C. on East side
of Kettle Lake. Found Both Orig.
B.T. Y. Pine 16 N 42 E 32 lks
Hem. 6 S 32 E 10 "
This W.C. to M.C. is set 20
lks. East of M.C. Distance
1/4 Cor. to M.C. is 2.27 Chs.

Bearing: S 78 - 42 W.

8.00 " Over lake.
12.43 " To road North and South and
old Dam to The North.
14.40 " To East Shore of Deep Woods
Lake.
16.40 " Over Lake to West shore.
18.77 " Distance W of M.C. to W 1/16
Cor. Did not set this cor.
because it would not agree
with the old Cor. because he
did not use the M.C.
39.81 " Through mixed Hwds. to Sec.
Cor. 11-14-15-10.

North Bet. Sec. 10 - 11.

Bearing: N 1 - 57 E.

18.04 " Set S 1/16 Cor.
25.50 " Enter open swp.
30.00 " Leave swp. for stand of old
Hwds. and second growth Hwds.
36.08 " To orig. 1/4 Cor.
Orig. Birch 16 N 75 E 21 lks
Roots of Hem. NW. New:
Hem. 8 S 70 W 45.9 lks.

North Bet. Sec. 10 - 11 Cont.

Bearing: N 2 - E 4 E.

8.00 Chs. Enter small Tan. swp.
11.00 " Leave swp.
21.98 " Set N 1/16 Cor. in E & W
Game Refuge Line, & follow
fence North.
30.72 " To fence West.
38.00 " Enter Spruce & Tan. Swp.
45.96 " To Sec. Cor. 2-11-10-3. Found
old stake in fence Cor. Fence
East and South. Found old Tan.
B.T. Stub 7 S 48 W 22.9 lks.

West Bet. Sec. 2 - 11.

Bearing: S 79 - 51 W.

20.79 " Set E 1/16 Cor. which agrees
with old fence N 8 S 4 E.
Clearing South of line and
Aspen and W. Birch to the N.
41.58 " To 1/2 Cor. in North & South
road. Four in. Galv. iron
pipe. No B.T. Set W.C.
40 lks. West.

Bearing: N 49 - 58 W.

20.485 " Along fence and set W 1/16 Cor.
31.00 " Enter swamp.
40.97 " To Sec. Cor. 2-11-10-3.

North Bet. Sec. 2 - 3.

Bearing: N 2 - 18 E.

20.625 " Leave swp. and set S 1/16 Cor
in Clear Lake road. Runs N&W.
Cedar W.C. Set 30 lks South.
Birch 5 S 75 W 34.6 lks.
Birch 8 N 43 E 47.7 "
41.25 " To 1/2 Sec. Cor. Found iron pin
for Cor. And an old B.T.
Birch 22 S 74 E 25.8 lks.

North Bet. Sec. 2 - 3, Cont.

Bearing: N 7 - 26 W

11.75 Chs. Enter Spruce swamp.
21.74 " Set the N 1/16 Cor.
43.56 " To Sec. Cor. 35-2-3-34, on
North Town Line.

West Bet. Sec. 22 - 27.

Bearing: S 86 - 03 W.

5.00 " Enter small swamp.
7.00 " Leave swp.
20.47 " Set N 1/16 Cor. This agrees
with an old stake we found
here.
30.00 " Enter small clearing.
40.94 " To 1/4 Cor. in old fence cor.
and on North edge of road.
Galv. iron pipe for cor.

Bearing: N 86 - 35 W.

1.00 " Enter open Spruce Swp.
5.00 " Leave swp.
8.00 " Enter farmers yard.
10.00 " To N & S Town road.
15.00 " Leave clearing.
18.00 " Enter Spruce swp.
20.095 " Set N 1/16 Cor. in Swp.
30.00 " Leave swp.
40.19 " To Sec. Cor. 22-27-28-21.
Galv. iron pipe by Co.
Surveyor and Hen. 14 S 20 lks
New. Birch 9 N 15 E 66 lks
Stone N 88 W 68 lks.

North Bet. Sec. 21 - 22.

Bearing: N 1 - 02 E.

2.00 " To edge of swp. and old road.
6.00 " Leave Swp.
17.00 " Enter Spruce and Tan. Swp.
20.085 " Set S 1/16 Cor. in Swp.
28.00 " Leave swp.
32.00 " Enter old swamp shore of
lake to the East.
34.00 " Leave swp.
40.17 " To 1/4 Cor. on East edge of swp.
Found old Stake and Orig. Tan.
7 N 61 W 28 lks. New; Stone
S 55 E 37.5 lks.
Maple 7 N 13 W 24.6 lks.

North Bet. Sec. 21 - 22 Cont.

Bearing: N 2 - 16 E.

1.90 Chm. To pond.
8.00 " Over pond.
9.00 " Leave Swamp.
12.50 " To South shore of lake. Could
not find N.C. and did not set
this N.C. because this lake
included in meander of Bogus
Marsh.
26.00 " Over lake
27.90 " Leave swp.
34.00 " Enter Spruce and Tam. Swp. and
Creek bottom with Tag Alders.
38.00 " Cross Creek 20 lks. wide and
flows almost South.
39.99 " To Sec. Cor. 15-22-21-16, on
East bank of creek. Found old
stake and both Orig. B.T.
Spruce 8 S 70 E 14 lks is White
Pine. Spruce 6 N 45 W 27 lks.
is down. Set new B.O.
Cedar post 10 S 65 W 21.2 lks
Cedar " 10 N 28 E 12.9 "

West Bet. Sec. 15 - 22.

Bearing: S 89 - 57 W.

4.75 " Cross old logging road N & S.
41.00 " To 1/2 cor. on West edge of the
Swp. Bogus Marsh. Found old stake
and mark up by D. B. Edick.
New: Hem. 15 S 81 W 9.2 lks.
Tam. 8 N 72 E 51.7 "

Bearing: N 85 - 57 W.

1.00 " Leave swp. at once.
3.50 " Cross town road N & S.
6.00 " Over ridge into swp.
8.00 " Leave swp.
8.00 " Enter same swp.
12.00 " To North end of island in Swp
15.00 " Leave island.
18.50 " Leave Swamp.
19.46 " Set N 1/16 Cor.
35.50 " Enter Tag Alders & Creek bottom.
38.92 " To sec. Cor. 15-22-21-16, on
East bank of Creek.

North Bet. Sec. 15 - 16.

Bearing: N 2 - 18 E.

- 3.00 Chm. Cross Creek Flows SW 20 lks wide.
 10.10 " Leave swp. for mixed woods.
 19.935 " Set S 1/16 Cor.
 27.00 " Enter Swamp.
 34.30 " Leave swp. and old tote road East & West.
 39.87 " To 1/2 Cor. Reset this 1/2 Cor. from tie in to N 1/16 Cor. and found old mark up about one foot North and roots of Orig. Hem. N 52 W 16 lks.
 New: Ash S 12 E 13.6 lks.
 Stone S 60 W 24.5 lks.

Bearing: N 2 - 17 E.

- 19.00 " Enter onto old logging road runs SW & North.
 20.285 " To old N 1/16 Cor. with B.T. Cedar 6 S 53 W 16 lks.
 20.80 " Enter old Cedar swp.
 22.00 " Cross Creek 10 lks wide and flows NE.
 24.00 " Leave swp.
 29.00 " Cross trail East & West.
 33.00 " Enter Cedar Swamp.
 40.57 " To Sec. Cor. 10-15-16-9. Old stake and both orig. B.T. Cedar 12 S 85 E 12 lks.
 Tan. 14 N 48 W 24 lks. but down under fallen trees.

West Bet. Sec. 10 - 15.

Bearing: S 89 02 W.

- 20.38 " Set E 1/16 Cor. on West edge of recent slashing. Small lake just North of this cor.
 40.76 " Set the 1/2 cor. on prop. Could not find any old cor. at all. Stone N 60 E 39.2 lks.
 Stone N 85 W 26.6 "
 61.14 " Set W 1/16 Cor.
 63.00 " Enter old Cedar Swp.
 71.50 " Cross Fire Lane NW & SE.
 81.52 " To Sec. Cor. 10-15-16-9.

North Bet. Sec. 9 - 10.

Bearing: N 2 - 40 W.

- 8.80 Obs. Cross Fire Lane NW & SE.
- 15.00 " Leave swp.
- 19.19 " Set S $1/16$ Cor. on Aspen ridge.
- 24.00 " Enter Cedar Swp.
- 33.00 " Leave Cedar Swp. for. old burnings.
- 38.30 " To orig. $\frac{1}{4}$ Cor. Found old stake and one Orig. B.T.
W. Pine Stp. 10 N 80 W 16 lks

Bearing: N 5 - 02 E.

- 5.00 " To South shore of Fox lake.
- 15.00 " Over lake into Swp. (wet)
- 21.41 " To N $1/16$ Cor. old stake and a B.T. Used this Cor. to set the Sec. Cor. North of here.
- 22.00 " Leave wet swamp.
- 24.00 " Enter old burned marsh.
- 28.00 " Leave marsh.
- 35.30 " Cross Fire Lane NE & SW.
- 37.00 " Enter very wet marsh.
- 40.80 " Leave marsh.
- 42.82 " Set Sec. Cor. 3-10-9-4, from N $1/16$ & $\frac{1}{4}$ Corners.
Pine Stp. 40 N 78 W 50.9 lks
Stone S 87 E 80.5 lks.
West Bet. Sec. 3 - 10.

Bearing: S 88 - 53 W.

- 8.25 " Leave swp. for old burnings with Aspen & Cherry.
- 41.91 " To M. C. set by Co. Surveyor. This Cor. holds platting on East side of the Lake. Large Summer Lodge and lawn just East of this Cor. Set Stone B.O. S 54 W 29.4 lks. 19.4

Bearing: S 88 - 52 W.

- 27.67 " Over Clear Lake, to West M.C. which is orig. Found stake and Orig. Hem. 12 S 54 E 13 lks.
Hem. 12 N 55 W 12 "

Bearing: N 85 - 55 W.

- 6.00 " Cross Fire Lane N & S.
- 14.05 " To Sec. Cor. 3-10-9-4.

North Bet. Sec. 3 - 4.

Bearing: N 7 - 16 E.

9.00 Chs. To Fire Lane NW & SE.
13.00 " Enter open Spruce swamp.
20.535 " Set S 1/16 Cor. in Swp.
41.07 " To $\frac{1}{4}$ Cor. Found old well
pipe for Cor. B.T.
Tan. 4 N 38 E 30.1 lks.

Bearing: N 1 - 23 W.

4.00 " To point of high land.
8.00 " Over point into swp.
18.00 " Leave swp. for badly burned
low Ground.
19.90 " Set N 1/16 Cor.
39.94 " To Cor. 34-3-4-33 on North
Town Line.

West Bet. Sec. 21 - 28.

Bearing: N 83 - 40 W.

12.87 " To East M.C. on Lake. Found
Orig. B.T. Birch 10 N 43 E 7
lks, but found it to be NW.
New: Maple 12 S 24 E 21.9 lks
Stone N 28 W 27 lks.

Bearing: N 88 - 36 W.

14.39 " Over lake to West M.C. Both
Orig. down and rotten but
show some of the axe work.
New: Hem. 8 N 23 W 31 lks.
Hem. 7 S 75 W 37.2 "

Bearing: N 89 - 56 W.

13.60 " Through Swp. & Swp. Conifers
and leave swp.
15.58 " To $\frac{1}{4}$ Cor. on top of ridge.
Found Galv. iron pipe by Co.
Surveyor and old B.T.
Hem. 12 N 24 $\frac{1}{2}$ E 59 lks.

Bearing: N 88 - 36 W.

1.50 " Cross private road.
7.00 " Cross Creek 10 lks wide flows SW.
20.465 " Set E 1/16 cor & leave clearing
for fair stand of Hws.
40.93 " To Sec. Cor. 21-28-29-20. Galv.
iron pipe by Co. Surveyor.
Old Elm 10 S 65 $\frac{1}{2}$ W 17 lks.

North Bet. Sec. 20 - 21.

Bearing: N 4 - 59 W.

1.00 Chs. Old logging road E & W.
19.695 " Set S 1/16 Cor.
21.00 " Cross old logging road E & W.
39.39 " To 1/4 Cor. Found orig. B.T.
Old Ironwood 9 S 44 E 11 lks
Birch 11 N 73 E 12 lks.
New Maple 12 N 17 E 31.9 lks.
Stone SE 1.6 lks.

Bearing: N 3 - 46 E.

20.985 " Set N 1/16 Cor. This line
all through good stand of Hwds.
32.11 " To South M.C. Re-set this
M.C. from work by E. S. Brooks.
and old mark up that looks
like D. B. Edick's. Set Cor.
5 feet North of mark up.
B.T. W. Pine 15 S 40 W 45.3 lks
Hem. 15 S 46 E 70.5 lks.

Bearing: N 11 - 06 E.

9.86 " To Sec. Cor. 16-21-20-17
in the lake.

West Bet. Sec. 16 - 21.

Bearing: N 88 - 36 W.

0.10 " Cross Creek 20 lks wide flows
South.
3.50 " Leave Tag Alders.
7.50 " Edge of swp. with pond in it.
13.50 " Leave swp.
19.66 " Set E 1/16 Cor. and enter Virgin
Timber South of the line.
39.32 " To orig. 1/4 Cor. Found stake and
Orig. Hem. 20 S 38 W 20 lks.
New: Hem. 9 N 61 E 34.7 lks.
Hem. 20 S 82 W 60.8 lks.

Bearing: N 87 - 23 W.

14.00 " To Pond
22.76 " Distance to W 1/16 Cor.
in pond.
33.70 " Over pond
38.40 " Enter swp. (Spruce)
42.35 " To M.C. on East side of lake.
Found orig. SE B.T. but is
down Tan. 10 S 75 E 64 lks.
New: W. Pine 18 N 30 E 51.9 lks.
W. Pine 10 S 49 E 39.6 lks.

West Bet. Sec. 16 - 21 Cont.

Bearings: N 82 - 25 W.

3.17 Chs. To Sec. Cor. 16-21-20-17 in 1
Lake.

North Bet. Sec. 16 - 17.

Bearings: N 11 - 06 E.

3.72 " To M.C. On North side of lake
Found both Orig. B.T.
Tan. 14 N 31 W 33 lks.
Tan. 12, N 36 E 26 "
New. W. Pine 7 N 27 E 46.2 lks
W. Pine 8 N 21 W 39.1 "

Bearings: N 0 - 04 E.

6.10 " Leave swp.
181.00 " Enter Spruce & Tan. Swp.
20.385 " Set S 1/16 Cor. in swp.
25.00 " Leave Swp.
36.70 " Enter Cedar & Spruce swp.
40.77 " Set 1/2 Cor. on prop. in Swp.
B.T. Cedar 7 S 75 W 14.4 lks.
Cedar 7 N 70 E 13 "
45.00 " Leave Cedar Swp.
52.50 " Enter Cedar Swp.
55.50 " Leave Swp.
61.155 " Set N 1/16 Cor. in Hwd.
reproduction.
78.50 " Leave Hwds. for Swp.
81.54 " To Orig. Sec. Cor. 9-16-17-8.
Found Orig. Birch 14 S 27 E 25
New: Cedar post S 52 E 11.5 lks.
Cedar post N 37 W 12.5 "

West Bet. Sec. 9 - 16.

Bearings: N 89 - 58 W.

7.00 " Leave Cedar Swp.
20.23 " Through second growth Hwds.
and set E 1/16 Cor.
22.00 " Enter low ground B. Ash.
40.46 " To 1/2 Cor. B.T.s all gone
found old stake with stone at
base. New, Hem. 12 S 17 W 27.7

West Bet. Sec. 9 - 16 Cont.

Bearing: N 84 - 29 W.

23.63 Chs. Set W 1/16 Cor.
Rem. 15 N 60 E 15.4 lks.
39.60 " Enter old grassy swamp.
47.26 " To Sec. Cor. 9-16-17-8.

North Bet. Sec. 8 - 9.

Bearing: N 2 - 20 E.

6.00 " Cross Fire Lane.
15.60 " Cross Creek 20 lks wide and
flows NE.
20.065 " Set S 1/16 Cor.
23.50 " Hit point of land.
24.50 " Leave point enter same swp.
27.00 " Leave Swp.
40.13 " To 1/2 Cor. Set this Cor. on
prop. and B.O. are
Y. Birch 6 S 73 1/2 E 16.8 lks.
Light grey rock S 17 W 50.4 "
60.195 " Set N 1/16 Cor. All this
through mixed Hwds.
64.00 " Enter Creek bottom.
65.25 " Creek 20 lks. wide flows West
66.00 " Leave Creek bottom for open
burnings.
71.00 " Enter Swp.
74.00 " Leave swp.
80.26 " To Sec. Cor. 4-9-8-5. And enter
Swamp. Found Orig. Tam. 6 S 24
W 20 lks. To be A Y. Birch.
New. Rem. 14 N 62 1/2 E 30 lks.
Rem. 18 N 24 W 40.9 "
Granite Boulder S 2 1/2 E 22.8 "

West Bet. Sec. 4 - 9.

Bearing: N 87 - 31 W.

21.587 " Set E 1/16 Cor.
36.00 " Enter Tam. Swp.
43.175 " Set 1/2 Cor on prop. in swp.
Tam. 5 N 45 W 16.8 lks.
Tam 5 S 80 E 34.5 "
44.20 " Leave Swp.
57.30 " Enter Cedar Swamp.
64.762 " Set W 1/16 Cor. On highland
point from NE.
74.50 " Enter onto high point of
land
86.35 " To Sec. Cor. 4-9-8-5 at edge
of swp.

North Bet. Sec. 4 - 5.

Bearings: N 16 - 33 E.

18.60 Chs. Leave Cedar Swp.
20.33 " Set S 1/16 Cor. in old burnings
40.66 " To 1/2 Cor. Found well pipe for
Cor. W.C.s to Cor.
Stone N 37 W 19.4 lks.
Iron pipe S 25 W 10.9 lks.

Bearing: N 2 - 33 W.

1.90 " Enter wet open swp.
6.00 " Over Swp.
11.90 " Enter Spruce swp.
21.61 " Set North 1/16 Cor. in Swp.
22.90 " Leave Spruce Swp.
26.00 " To old RR. grade NE & SW.
29.00 " Enter small Tam. & Spruce
swamp.
34.00 " Leave swp.
43.90 " To Cor. 33-4-5-32-on North
Town Line.

West Bet. Sec. 20 - 29.

Bearing: N 88 - 37 W.

1.00 " Cross Fire Lane N & S.
6.00 " Enter Swp. (Cedar, Balsam Spruce)
20.585 " Set E 1/16 Cor.
41.17 " To 1/2 Cor. Found old Stake and
B.T. Cedar 12 N 26 E 28.5 lks
New. Cedar 9 S 23 E 14.9 "
Cedar 7 N 88 W 24 "

Bearings: N 88 - 58 W;

20.58 " To old logging road and set
on East side of the road.
Logging road runs NW and SE.
41.16 " Through Spruce swamp to Sec.
Cor. 20-29-30-19 in swp.
Found old stake and Both Orig.
Cedar 11 S 21 W 9 is Tam.
Tam. 10 N 63 E 15 lks is SE.
New. Cedar 7 S 62 W 35 lks.
Cedar 6 N 15 W 36.7 "
Spruce 8 S 47 W 21.5 "

West Bet. Sec. 19 - 30.

Bearing: N 87 - 31 W.

2.00 Chs. Cross logging road N & S.
45.00 " To open slashing.
19.77 " Set the E 1/16 Cor.
24.10 " Cross creek 5 lks. wide flows SE.
30.00 " Leave Cedar swp. for low
land Hds.
39.54 " To $\frac{1}{2}$ Cor. Found and old Tan,
that had been registered on
and a Soft Maple NW of it
with axe work. This also agrees
very close with Govt. distance
to the creek West of here.
Set $\frac{1}{2}$ Cor. bet. these trees.
S. Maple 6 N 40 W 27.5 lks.
S. Maple 8 N 79 E 36.8 "

Bearing: S 86 - 57 W.

4.25 " Cross West branch of the
Eau Claire River 25 lks wide
and flows South.
20.89 " Set West 1/16 Cor. in low
ground.
41.47 " Through low ground to Sec. Cor.
19-30-25-24 on West Range Line.

North Bet. Sec. 19 - 20.

Bearing: N 0 - 03 E.

20.225 " Set South 1/16 Cor. in Swp.
40.45 " Set $\frac{1}{2}$ Cor. on prop. Could not
find any thing of a Cor. A
well blazed line North of the
 $\frac{1}{2}$ Cor. and very close to our
line. Set New B.T.
Cedar 6 N 34 E 16.2 lks.
Cedar 8 S 47 E 27.3 "
52.00 " Leave Cedar Swp. for low ground.
60.675 " Set North 1/16 Cor.
71.00 " Cross old logging road NE & SE.
and enter Cedar swamp.
80.90 " To Sec. Cor. 17-20-19-18.
Found Orig. Cedar 6 S 43 W 48
lks. to be NW. Set New B.T.
Cedar Stp. 12 N 67 W 20.2 lks.
Cedar " 14 N 35 E 33.0 "
Tan. " 20 S 55 W 26.1 "

West Bet. Sec. 17 - 20.

Bearing: N 82 - 25 W.

1.30 " To M.C. on West side of lake.
Orig. Tan. 10 S 76 W 29 standing.
New W. Pine 15 S 60 E 4.5 lks.
W. Pine 14 N 75 W 52.5 "

West Bet. Sec. 17 - 20 Cont.

Bearing: N 88 - 44 W.

- 2.00 Chs. Leave Swp. around lake, and
enter fair stand of mixed Hwds.
20.53 " Set E 1/16 Cor.
37.00 " Cross Fire Lane very close to
the gate.
41.06 " Set $\frac{1}{4}$ Cor. on prop. This cor.
has been gone for over 40 years.
B.T. Birch 16 S 18 W 30.6 lks.
Stone N 23 W 32.8 lks.
61.00 " Cross old road N & S.
61.59 " Set West 1/16 Cor.
63.00 " Enter large Cedar Swp.
82.12 " To Sec. Cor. 17-20-19-18.

West Bet. Sec. 18-19.

Bearing: N 89 - 38 W.

- 9.50 " To point of high land.
13.20 " Over point.
20.07 " Set E 1/16 Cor.
37.50 " Leave swp. for low ground.
40.14 " Set $\frac{1}{4}$ Cor. on prop. Found
a few old line blazes
East, West, North and South.
Y. Birch 20 S 45 E 9.0 lks.
Y. Birch 14 N 41 W 6.0 ".
60.21 " Set W 1/16 Cor.
76.50 " Leave low ground for Creek
bottom.
78.50 " Cross Creek 20 lks wide
flowing South.
80.51 " To Sec. Cor. 18-19-24-13, in
another Creek from the West.
This Cor. on West Range Line.

North Bet. Sec. 17 - 18.

Bearing: N 1 - 46 E.

- 19.97 " Set South 1/16 Cor.
39.94 " To Orig. $\frac{1}{4}$ Cor. Found Orig.
B.T. Cedar 12 S 87 W 17 lks
No marks. Motten windfall.
Cedar 10 N 66 E 10 lks. this
tree remarked by unknown person
New! Cedar 6 N 37 E 11.2 lks.
B. Ash 6 N 35 W 28 "

North Bet. Sec. 17 - 18 Cont.

Bearing: N 1 - 09 W.

7.30 Chs. Leave large Cedar Swp.
11.50 " Cross Fire Lane NW & SE.
20.645 " Set North 1/16 Cor.
31.30 " Enter Spruce and Tam. Swp.
41.29 " To Sec. Cor. 8-17-18-7. Found
old stake but no B.T. This
Corner has been used for a
long time. New B.T.
Tam. 6 S 82 E 39.7 lks.
Tam. 8 S 68 W 89.2 "
Tam. 5 N 32 W 93.2 "

West Bet. Sec. 8 - 17.

Bearing: N 88 - 56 W.

4.00 " Leave old Swp.
18.00 " Enter narrow open marsh.
Long North & South.
20.15 " Set East 1/16 Cor. on West
edge of marsh and leave same.
40.30 " To 1/4 Cor. Found badly burned
Stps. of Orig. which show axe
work. Cor. on North bank of wet
ravine which runs E & W.
New: W. Birch 6 S 23 E 16.5
Cedar stp. 16 N 56 W 107

Bearing: N 88 - 22 W.

8.00 " Enter wet open marsh supposed
to be Lake.
12.00 " To South point of lake.
20.00 " Leave wet marsh.
39.50 " Enter Tam. and Spruce swp.
42.25 " To Sec. Cor. 8-17-18-7.

West Bet. Sec. 7 - 18.

Bearing: S 89 - 41 W.

9.00 " Cross old logging road NW & SE.
10.00 " Leave Swp. for young Hwds.
20.005 " Set East 1/16 Cor.
40.01 " To 1/4 Cor. Found old stake with
rock around the base.

West Bat. Sec. 7 - 18.

Bearing: S 88 - 29 W.

- 1.00 Chs. Cross Fire Lane which bears
SE, about 4 chs. South where
Fire lanes join.
5.00 " Cross Fire Lane SW & NE.
18.70 " Set West 1/16 Cor.
26.00 " Cross Creek 20 lks wide
and flows South.
32.50 " Enter old burned swp.
38.53 " To Sec. Cor. 7-18-13-12. on
West Range Line.

North Bat. Sec. 7 - 8.

Bearing: N 3 - 34 E.

- 1.50 " Leave Swp. for Aspen and
mixed Hws.
19.97 " Set South 1/16 Cor.
26.50 " Cross Fire Lane E & W.
27.50 " Cross Creek 20 lks wide
flows West.
34.50 " Enter Alder Swp.
35.89 " Leave Swamp
39.94 " Set 1/2 Cor. on prop.

59.91 " Set North 1/16 Cor.
60.20 " Enter Creek bottom.
61.00 " Creek 20 lks. wide flows NE.
61.50 " Leave Creek bottom.
75.00 " Enter Tam. Swp.
78.50 " Leave Tam. Swp.
79.88 " To Sec. Cor. 5-8-7-6, Set
on prop. from other Govt. Cor.
W. Birch 5 S 85 E 22.9 lks.
W. Birch 6 N 24 W 19.1 "
Stone N 50 E 81 lks.

West Bat. Sec. 5 - 8.

Bearing: N 89 - 50 W.

- 5.40 " Cross Creek 20 lks wide
and flows South, through
hay marsh.
11.90 " Leave Creek bottom & hay marsh.
20.225 " Set East 1/16 Cor. in slashing.
21.60 " Cross Fire Lane N & S.
39.50 " Enter Spruce and Tam. swp.
40.45 " To Orig. 1/2 Cor. Found Orig.
Tam. stub S 27 W 25 lks.
Cedar Stp. North 18 lks.
New: Cedar stp. 12 S 25 E 13.5
lks.

West Bet. Sec. 5 - 8 Cont.

Bearing: N 87 - 31 W.

17.35 Obs. Leave swp.
20.235 " Set W 1/16 Cor.
24.00 " Enter swp. & swp. Hnds.
29.50 " To lake at outlet.
34.00 " To West shore and follow close
to shore. No swp. here.
40.47 " To Sec. Cor. 5-8-7-6.

West Bet. Sec. 6 - 7.

Bearing: N 89 - 02 W.

0.50 " Enter narrow swp.
1.50 " Leave swp.
20.03 " Set East 1/16 Cor.
40.06 " Set, $\frac{1}{2}$ Cor. on prep.
Stone S 75 E 25.4 lks.
Stone N 50 E 10.3 "
40.50 " Enter small swp.
44.00 " Leave swp.
60.09 " Set West 1/16 Cor.
81.47 " To top of hill and Sec. Cor.
6-7-12-1, on West Range Line.

North Bet. Sec. 5 - 6.

Bearing: N 5 - 46 E.

19.975 " Set South 1/16 Cor.
34.00 " Enter narrow swp.
39.95 " To Orig. $\frac{1}{2}$ Cor. Found Orig.
Maple 15 S 25 E 16 lks. but
find it NW. New B.T.
Cedar 6 S 69 W 25.7 lks.
Cedar 6 N 30 W 20.1 "

Bearing: N 5 - 46 E.

14.00 " Leave swp.
20.10 " Set North 1/16 Cor. Random
line so far from true line
we can not give location
of swamps.
21.00 " Enter Creek bottom.
28.60 " Leave Creek bottom.
37.60 " Creek 10 lks wide flows SE.
40.63 " To Sec. Cor. 32-5-6-31, on
North Town Line.

This is to certify that I,
D.A. Hints, have made this Survey,
a retracement of the Original
Government Field work in this
Township with the aid of recorded
County Survey notes on record in
the County Clerks Office of
Langlade County, State of Wisconsin
and Original Government Field Notes.

All bearings are True
Bearings calculated from a Polaris
observation and all Sections were
closed by computing latitudes and
departures and found to be correct.

I have done this work to
the best of my knowledge and in
compliance with the U.S.G.L.O.
manual.

D. A. Hints.
May 11, 1939.

Instruments used.

- 1 Dietzgen Light Highway Transite,
in good condition.
- 1 Dietzgen 200 link steel tape,
in good condition.
- 1 Dietzgen 100 foot steel tape,
in good condition.
- 1 Set of chaining pins and a
Range pole.

Section corners and $\frac{1}{4}$ corners are
set with 4" boiler tubing filled
with concrete surmounted by a
brass cap, on which is stamped
the corner location.

All $1/16$ corners are set with Cedar
posts and their location inscribed
on them.