

552280' N 89° 17' E - 3987 ch.
(Line Data from a 1930-40 survey.)
156.29' by W.P.A.-GOV.
211'-46'

Coord.
N. 5, 221.63'
E. 115.48'

Exception.

Joseph Ploederl
To D.N.R.

Joseph Ploederl
To D.N.R.

NE-SW.

NW-SE.

center Line.

Anton
Augustyn
Squaw
Creek
10 ACROSS

1659.11' ^{Fir} Hub - Top of Knoll.
1574.36' Bottom of Hill - Hub.

Line point. B.C.I.P. 1-2" wide feeder Grk
 coord. 12" x 40 orange 1 P. 24 W
 N 14 60 98' 14 E to pond
 W 868.08' NW B.T. 16 CW - N 31 W - 54.9 ft
 NW B.T. 22 CW - N 60 E - 3.1 (old blazed)
 Anton Augustyn.

SE-SW.

(Note: In the 1930's a W.P.A. Project survey of this section 25 was made, along with several others. I computed the $N-S \frac{1}{4}$ line from the $E \frac{1}{2}$ and the $W \frac{1}{2}$ of their section survey. My actual bearing and distance on this $N-S \frac{1}{4}$ line checks out well with their $E \frac{1}{2}$ of Sec. 25. They made an error of several feet in their $W \frac{1}{2}$ of Sec. 25, as shown by the $N-S \frac{1}{4}$ line closure.)

WISCONSIN
ROBERT L. HIG
WOODRUFF
WIS
5-614
LAND SURVEYOR

scale: 1" = 200'
Date: May, 1972

Surveyor:
Robert L. Ilg

Cor. on N. edge of E-W Di. ke - at water's edge
(orig. perp.) Di. ke bears 584° W.
New B.T. 13" MR - N84° E - 85.5'
New B.T. 21" BY - N60° E - 97.2'
E of N end of CURVE is E. 73.5'
54 Cor. is a 3" B.C.I.R. - 15" up - by County.

589-22'E. (Data from a 1930 to 40 survey.)
41.12 ch. by W.P.A. - Govt.

SURVEY FOR THE DEPT. OF NATURAL
RESOURCES- PART OF THE SE-NW & PART OF
THE NE-SW OF SEC.25-T33N-R12E- LANGLEADE COUNTY, WIS.

25-33-12

RECORD # 40026 (EXTRA)
 LANGLADE COUNTY SURVEYORS OFFICE
 DATE FILED: _____ BY: _____

Perp. Orig. N 1/4 cor.

N 87° 17' E - 3987 ch.

(Line Data from a 1930-40 survey.)
by W.P.A.-Gov.

A 3" Brass Cap Iron pipe - 12" up.
by Langlade County.
New B.T. MH 6" - N 88° E - 33.8'
New B.T. MH 7" - N 21° E - 39.8'
old rotten 20" MH 5" - N 68° E - 22 1/2 LK
(No marking still visible)
old Beaver flowage to the West is
now dried up.

Coord.
N 5221.63'
E 115.48'

5222.88'

318.52'

105° 50'

5004.2'

4505.23' - 2 1/2" Maple Hub.

4257' Ctr. Spring area.

4099' - E of 3 ft. crk - Flows NW.

3960' in spring area.

3628.22' Fir Hub up on rise.

3498' Enter Aspen. (6-9")

3432' LV. SWP.

3339.20' Fir Hub in SWP.

5004.1977'

2784.14' Nail on N. edge of
8" Aspen Stp. (SWP)


2646' No hub - only a blaze on a
4" fir just E. of line.

2219.51' Ash Hub in SWP.

1659.11' Fir Hub - Top of Knoll.

1574.36' B. Hom. of Hill - Hub.

1191.17' Fir Hub



Scale: 1" = 200'
Date: May, 1972.
Surveyor:
Robert L. Ilg

G. Skidmore

Exception.

SE-NW.

Joseph Ploederl
To D.N.R.

Joseph Ploederl
To D.N.R.

NE-SW.

NW-SE.

1/6 th. Line Not run.

W. to Center
of Squaw
Creek =
44 1/2 ft.

R.O.B.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

79.1542' - Calc. from E 1/2 of Sec. 25 Data (-1930 to 40 W.P.A. Map) - Declination 2-25'E.

5222.88'

79.1346' ch.

West parallel
to S. Side of
1/6 th. Sec.

Coord.
N 1452.14'
E 11166.01'

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

D.N.R.

Line point.
1 1/2" Brass Cap I.P. 4' long & 8" up.
New B.T. 14" Hem. N 24° W - 74.0 ft.
New B.T. 13" MH 528' W - 71.2'
12 1/2' W. to E. of road.
Coord. N 1460.98'
E 868.08'
Line is blazed
14' E to pond
New B.T. 16" CW - N 31° W - 54.9 ft.
New B.T. 22" CW - N 60° E - 3.1' (old blazed).
Anton Augustyn.

SE-SW.

True North - South 1/4 line.

4° 31'

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

429.97'

Hub.

Cor. on N. edge of E-W DiKE - at water's edge.
(Orig. Perp.) DIKE bears 584° W.
New B.T. 13" MR - N 84° E - 85.5'
New B.T. 21" By - N 60° E - 97.2'
E of N. end of culvert is E. 73 1/2'
54 Cor. is a 3" B.C.I.P. - 15" up - by County.
589° 22' E. (Data from a 1930 to 40 survey.)
by W.P.A.-Govt.

Coordinates
are N 0.000
E 0.000

SURVEY FOR THE DEPT. OF NATURAL
RESOURCES - PART OF THE SE-NW & PART OF
THE NE-SW OF SEC. 25-T.33N-R.12E-LANGLADE COUNTY, WIS.

AINSWORTH # 1
T 33N R. 12E

RECORD # 40028
LANGLADE COUNTY SURVEYORS OFFICE
DATE FILED 6/4/93 BY: D.T.